

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PREMA MONTAGE FLUID

Art.-No.

PMF-5000 (SKU No. 2201020)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Agent to fit on tyres

1.3. Details of the supplier of the safety data sheet

Company name: PREMA GmbH
Street: Aspertsham 40
Place: D-94081 Fürstenzell
Telephone: +49 (0) 8502 917 150 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a

week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Additional advice on labelling

The product does not require a hazard warning label in accordance with EC directives/the relevant national laws.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aqueous solution

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.



PREMA GmbH

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 2 of 8

After contact with skin

Wash off with soap and plenty of water.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids.

If eye irritation persists, consult a specialist.

After ingestion

Drink water as a precaution

In the event of symptoms refer for medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

May cause eye or skin irritation with susceptible persons.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.



PREMA GmbH

Print date: 03.06.2022



Safety Data Sheet

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 3 of 8

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with strong acids and oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Agent to fit on tyres

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
57-55-6	Propane-1,2-diol, total (vapour and particulates)	150	470		TWA (8 h)	

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

8.2. Exposure controls

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

Eye/face protection

Safety goggles with side protection (EN 166).

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, Minimum coat thickness 0.6 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)



PREMA GmbH

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 4 of 8

Respiratory protection

No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

Physical state: Liquid Colourless Odour: Mild PH-Value (at 20 °C): Mild PH-Value (at 20 °C): 11 - 12 Changes in the physical state Melting point/freezing point: approx. 0 °C Boiling point or initial boiling point and boiling point or initial boiling point and boiling point or initial boiling point and boiling point: n.d. Softening point: n.d. Pour point: n.d.	9.1. Information on basic physical and chemical properties							
Odour: Mild pH-Value (at 20 °C): 11 - 12 Changes in the physical state Melting point/freezing point: approx. 0 °C Boiling point or initial boiling point and approx. 100 °C boiling range: Sublimation point: n.d. Softening point: n.d. Pour point: n.d. Pour point: n.d. Flash point: n.d. Flash point: n.a. Sustaining combustion: Not sustaining combustion Flammability Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature: n.d. Self-ignition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm² Bulk density: n.a. Water solubility: Completely miscible (at 20°C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	Physical state:	Liquid						
pH-Value (at 20 °C): 11 - 12 Changes in the physical state Melting point/freezing point: approx. 0 °C Boiling point or initial boiling point and approx. 100 °C boiling range: Sublimation point: n.d. Softening point: n.d. Pour point: n.d. Flash point: n.d. Flash point: n.a. Sustaining combustion: Not sustaining combustion Flammability Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature: n.d. Self-ignition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Flowporation test: n.d. Flowlere subparation test: n.d. Flowlere subparation test: n.d. Flowlere subparation test: n.d.								
Changes in the physical state Melting point/freezing point: Bolling point or initial bolling point and bolling range: Sublimation point: Softening point: Pour point: Flash point: Sustaining combustion: Flammability Solid/liquid: Gas: The product is not explosive. Lower explosion limits: Auto-ignition temperature: Solid- Solid/lignid na. Self-ignition temperature: Solid: Cas: Decomposition temperature: Not sustaining combustion Flammability Solid/liquid: Gas: n.a. Cas: n.d. Upper explosion limits: n.d. Auto-ignition temperature: Solid: Solid/lignid na. Decomposition temperature: Non oxidizing. Vapour pressure: Density (at 20 °C): Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: N.d. Viscosity / dynamic: In.d. Relative vapour density: R.d. Relative vapour density: R.d. Solvent separation test: n.d. Solvent separation test: n.d. Solvent separation test: n.d. Solvent separation test: n.d.		Mild						
Melting point/freezing point: Boiling point or initial boiling point and boiling range: Sublimation point: Softening point: Pour point: In.d. Pour point: In.d. Flash point: Solid/liquid: Gas: The product is not explosive. Lower explosion limits: Upper explosion limits: Upper explosion limits: In.d. Self-ignition temperature Solid: Gas: Ras: Solid: Gas: In.a. Self-ignition temperature: Not sustaining combustion Ras. Self-ignition temperature: In.d. Oxidizing properties Non oxidizing. Vapour pressure: Density (at 20 °C): Bulk density: Water solubility: Gompletely miscible (at 20 °C) Partition coefficient n-octanol/water: Viscosity / kinematic: In.d. Flow time: Relative vapour density: In.d. Rol. Relative vapour density: In.d. Relative vapour density: In.d. Relative vapour density: In.d. Rol. Rol. Rol. Rol. Rol. Rol. Rol. Rol	pH-Value (at 20 °C):		11 - 12					
Boiling point or initial boiling point and boiling range: Sublimation point: Softening point: N. d. Softening point: Pour pour point: Pour pour point: Pour pour point: Pour pour pour pour pour pour pour pour p								
boiling range: Sublimation point: Softening point: n.d. Softening point: n.d. Pour point: n.d. Flash point: n.a. Sustaining combustion: Not sustaining combustion Flammability Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Self-Ignition temperature: Solid: Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: Non oxidizing. Vapour pressure: Nate of the product is not explosive. Completely miscible (at 20 °C): Bulk density: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: Evaporation tase: n.d. Solvent separation test: n.d.	• .		···					
Softening point: n.d. Pour point: n.d. Flash point: n.a. Sustaining combustion: Not sustaining combustion Flammability Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Self-ignition temperature: n.d. Self-ignition temperature: n.d. Self-ignition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation test: n.d. Evaporation test: n.d. Evaporation tase: n.d. Evaporation tase: n.d. Evaporation test: n.d.	boiling range:	d	approx. 100 °C					
Pour point: n.d. Flash point: n.a. Sustaining combustion: Not sustaining combustion Flammability Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature Solid: n.a. Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Flow time: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	•		n.d.					
Flash point: n.a. Sustaining combustion: Not sustaining combustion Flammability Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature: n.a. Gas: n.a. Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	- •							
Sustaining combustion: Flammability Solid/liquid: Gas: In.a. Explosive properties The product is not explosive. Lower explosion limits: I. d. Upper explosion limits: I. d. Auto-ignition temperature: Solid: Gas: I. a. Self-ignition temperature: Solid: Gas: I. a. Decomposition temperature: Non oxidizing properties Non oxidizing. Vapour pressure: I. d. Density (at 20 °C): Bulk density: I. a. Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: I. d. Viscosity / kinematic: I. d. Flow time: I. d. Relative vapour density: I. d. Evaporation rate: I. d. Solvent separation test: I. d. Solvent separation test: I. d. Solvent separation test: I. d. I. d. Solvent separation test: I. d. Solvent separation test: I. d. Solvent separation test: I. d. I. d.			n.d.					
Flammability Solid/liquid: Gas: In.a. Explosive properties The product is not explosive. Lower explosion limits: Iupper explosion limiter. Iupper explosion limite	·							
Solid/liquid: n.a. Gas: n.a. Explosive properties The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature Solid: n.a. Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	_		Not sustaining combustion					
Explosive properties The product is not explosive. Lower explosion limits: Upper explosion limits: n.d. Auto-ignition temperature: Solid: Gas: Decomposition temperature: Non oxidizing properties Non oxidizing. Vapour pressure: Density (at 20 °C): Partition coefficient n-octanol/water: Viscosity / dynamic: Nic. Flow time: Rod. Relative vapour density: n.d. Relative vapour density: n.d. Relative vapour density: n.d. Responsity (at 20 °C): Partition coefficient n-octanol/water: n.d. Relative vapour density: n.d. Solvent separation test: n.d. Solvent separation test: n.d. Solvent separation test: n.d. Ind.			n.a.					
The product is not explosive. Lower explosion limits: n.d. Upper explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature Solid: n.a. Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	Gas:		n.a.					
Upper explosion limits: n.d. Auto-ignition temperature: n.d. Self-ignition temperature Solid: n.a. Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Solvent separation test: n.d.								
Auto-ignition temperature: Self-ignition temperature Solid: Gas: Decomposition temperature: Non oxidizing properties Non oxidizing. Vapour pressure: Nater solubility: (at 20 °C): Partition coefficient n-octanol/water: Viscosity / dynamic: Nicosity / kinematic: Flow time: Relative vapour density: Nater solubility: (n.d. Viscosity / dynamic: N.d. Viscosity / kinematic: N.d. Relative vapour density: N.d. Solvent separation test: N.d. Solvent separation test: N.d. Nater solubility: N.d. Completely miscible N.d. Completely miscible N.d. N.d. N.d. N.d. N.d. N.d. N.d. N.d	Lower explosion limits:		n.d.					
Self-ignition temperature Solid: Gas: Decomposition temperature: Oxidizing properties Non oxidizing. Vapour pressure: Density (at 20 °C): Bulk density: Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: N.d. Viscosity / kinematic: Flow time: Relative vapour density: Evaporation temperature n.a. n.a. n.a. Completely miscible (at 20 °C) n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Solvent separation test: n.d.	Upper explosion limits:		n.d.					
Solid: n.a. Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	Auto-ignition temperature:		n.d.					
Gas: n.a. Decomposition temperature: n.d. Oxidizing properties Non oxidizing. Vapour pressure: n.d. Density (at 20 °C): approx. 1,0 g/cm³ Bulk density: n.a. Water solubility: Completely miscible (at 20 °C) Partition coefficient n-octanol/water: n.d. Viscosity / dynamic: n.d. Viscosity / kinematic: n.d. Flow time: n.d. Relative vapour density: n.d. Evaporation rate: n.d. Solvent separation test: n.d.	Self-ignition temperature							
Decomposition temperature: Oxidizing properties Non oxidizing. Vapour pressure: Density (at 20 °C): Bulk density: Na. Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: Na. Viscosity / kinematic: Flow time: Relative vapour density: Evaporation rate: Solvent separation test: n.d. n.d. n.d. n.d. n.d. n.d. n.d. n.d.								
Oxidizing properties Non oxidizing. Vapour pressure: Density (at 20 °C): Bulk density: Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: N.d. Viscosity / kinematic: Flow time: Relative vapour density: Evaporation rate: Solvent separation test: n.d.								
Non oxidizing. Vapour pressure: Density (at 20 °C): Bulk density: Nater solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: Nic. Viscosity / kinematic: Flow time: Relative vapour density: Evaporation rate: Solvent separation test: n.d. n.d. n.d. n.d. n.d. n.d. n.d. n.d. n.d.			n.a.					
Density (at 20 °C): Bulk density: Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: Viscosity / kinematic: Flow time: Relative vapour density: Evaporation rate: Solvent separation test: n.d. approx. 1,0 g/cm³ n.a. Completely miscible Completely miscible n.d. n.d. n.d. n.d. n.d. properties approx. 1,0 g/cm³ n.a. n.d. completely miscible n.d. n.d. n.d. n.d. n.d. solvent separation test: n.d.								
Bulk density: Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: N.d. Viscosity / kinematic: Flow time: Relative vapour density: Evaporation rate: Solvent separation test: n.a. Completely miscible Completely miscible n.d. n.d. n.d. n.d. n.d. n.d. n.d. n.d.	Vapour pressure:		n.d.					
Water solubility: (at 20 °C) Partition coefficient n-octanol/water: Viscosity / dynamic: Viscosity / kinematic: In.d. Flow time: Relative vapour density: Evaporation rate: Solvent separation test: Completely miscible n.d. n.d. n.d. n.d. Completely miscible n.d. n.d. n.d. n.d. Solvent separation test: n.d.	,		approx. 1,0 g/cm³					
(at 20 °C)Partition coefficient n-octanol/water:n.d.Viscosity / dynamic:n.d.Viscosity / kinematic:n.d.Flow time:n.d.Relative vapour density:n.d.Evaporation rate:n.d.Solvent separation test:n.d.	•							
Viscosity / dynamic:n.d.Viscosity / kinematic:n.d.Flow time:n.d.Relative vapour density:n.d.Evaporation rate:n.d.Solvent separation test:n.d.	(at 20 °C)		Completely miscible					
Viscosity / kinematic:n.d.Flow time:n.d.Relative vapour density:n.d.Evaporation rate:n.d.Solvent separation test:n.d.			n.d.					
Flow time: Relative vapour density: Evaporation rate: Solvent separation test: n.d. n.d. n.d. n.d.	Viscosity / dynamic:		n.d.					
Relative vapour density: Evaporation rate: Solvent separation test: n.d. n.d. n.d.	Viscosity / kinematic:		n.d.					
Evaporation rate: n.d. Solvent separation test: n.d.	Flow time:		n.d.					
Solvent separation test: n.d.	Relative vapour density:		n.d.					
	Evaporation rate:		n.d.					
	Solvent separation test:		n.d.					
	Solvent content:		< 5 %					



PREMA GmbH

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 5 of 8

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids and strong oxidising agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

10.5. Incompatible materials

Strong acids and oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

No toxical dates available.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Not classified. [OECD 431] (Analogy end)

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

May cause eye or skin irritation with susceptible persons.

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

Print date: 03.06.2022



Safety Data Sheet

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 6 of 8

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Slightly water hazardous.

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: No dangerous good in sense of this transport regulation.
 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
 14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number: No dangerous good in sense of this transport regulation.
 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
 14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)





according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 7 of 8

14.1. UN number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

2004/42/EC (VOC): < 20 %

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,6,7,8,9,10,11,12.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



PREMA GmbH

Print date: 03.06.2022

according to Regulation (EC) No 1907/2006

PREMA MONTAGE FLUID

Revision date: 03.06.2022 Product code: 00623-0033 Page 8 of 8

GHS = Globally Harmonized System of Classification and Labelling of Chemicals REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)