



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 1 of 12

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

PREMA BLACK VULC SOLUTION

##### Art.-No.

PBVS-32 (SKU No. 2205505)

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesive

##### 1.3. Details of the supplier of the safety data sheet

Company name: PREMA GmbH

Street: Aspertsham 40

Place: D-94081 Fürstzell

Telephone: +49 (0) 8502 917 150 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

##### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

##### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Skin Irrit. 2; H315

Repr. 1B; H360D

STOT SE 3; H336

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

##### Regulation (EC) No 1272/2008

##### Hazard components for labelling

Naphtha (petroleum)

Phenol, 4-(1,1-dimethylethyl)-, polymer with ethyne

Signal word: Danger

##### Pictograms:



##### Hazard statements

|       |  |
|-------|--|
| H225  | Highly flammable liquid and vapour.              |
| H315  | Causes skin irritation.                          |
| H336  | May cause drowsiness or dizziness.               |
| H360D | May damage the unborn child.                     |
| H411  | Toxic to aquatic life with long lasting effects. |

##### Precautionary statements

|      |  |
|------|--|
| P202 | Do not handle until all safety precautions have been read and understood.                      |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 2 of 12

|                |  |
|----------------|--|
| P260           | Do not breathe vapour.   |
| P262           | Do not get in eyes, on skin, or on clothing.   |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.                             |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                             |
| P312           | Call a POISON CENTER/doctor if you feel unwell.  |
| P301+P310      | IF SWALLOWED: Immediately call a doctor.   |
| P331           | Do NOT induce vomiting.  |
| P273           | Avoid release to the environment.  |

#### Special labelling of certain mixtures

|        |   |
|--------|---|
| EUH208 | Contains Di(benzothiazol-2-yl) disulphide, N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction.<br>Restricted to professional users. |
|--------|---|

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation solved in petroleum spirit

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**PREMA BLACK VULC SOLUTION**

Revision date: 23.04.2024

Product code: 00623-0040

Page 3 of 12

**Hazardous components**

| CAS No     | Chemical name  | Quantity     |                  |          |
|------------|--|--------------|------------------|----------|
|            | EC No  | Index No     | REACH No         |          |
|            | GHS Classification   |              |                  |          |
| 64742-49-0 | Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]               |              |                  | < 65 %   |
|            | 921-024-6  |              | 01-2119475514-35 |          |
|            | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411                 |              |                  |          |
| 64742-49-0 | Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane]  |              |                  | < 25 %   |
|            | 931-254-9  |              | 01-2119484651-34 |          |
|            | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411                 |              |                  |          |
| 1314-13-2  | Zinc oxide   |              |                  | < 1 %    |
|            | 215-222-5  | 030-013-00-7 | 01-2119463881-32 |          |
|            | Aquatic Acute 1, Aquatic Chronic 1; H400 H410  |              |                  |          |
| 28514-92-3 | Phenol, 4-(1,1-dimethylethyl)-, polymer with ethyne  |              |                  | < 1 %    |
|            | Repr. 1B; H360D  |              |                  |          |
| 120-78-5   | Di(benzothiazol-2-yl) disulphide   |              |                  | < 1 %    |
|            | 204-424-9  | 613-135-00-0 | 01-2119489366-24 |          |
|            | Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410 EUH031  |              |                  |          |
| 102-06-7   | N,N-Diphenylguanidine  |              |                  | < 1 %    |
|            | 203-002-1  | 612-149-00-4 | 01-2119519144-47 |          |
|            | Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 2; H361f H302 H315 H319 H335 H411 |              |                  |          |
| 793-24-8   | N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine   |              |                  | < 0,25 % |
|            | 212-344-0  |              | 01-2119485839-15 |          |
|            | Repr. 1B, Acute Tox. 4, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H360FD H302 H317 H400 H410             |              |                  |          |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No    | EC No  | Chemical name                                      | Quantity |
|-----------|--|--|----------|
|           | Specific Conc. Limits, M-factors and ATE   |  |          |
| 1314-13-2 | 215-222-5  | Zinc oxide   | < 1 %    |
|           | Aquatic Acute 1; H400: M=1<br>Aquatic Chronic 1; H410: M=1   |  |          |
| 120-78-5  | 204-424-9  | Di(benzothiazol-2-yl) disulphide                   | < 1 %    |
|           | Aquatic Acute 1; H400: M=1<br>Aquatic Chronic 1; H410: M=1   |  |          |
| 102-06-7  | 203-002-1  | N,N-Diphenylguanidine                              | < 1 %    |
|           | oral: ATE = 500 mg/kg  |  |          |
| 793-24-8  | 212-344-0  | N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine | < 0,25 % |
|           | dermal: LD50 = > 7940 mg/kg; oral: LD50 = 893 mg/kg Aquatic Acute 1; H400: M=10<br>Aquatic Chronic 1; H410: M=10 |  |          |

**Further Information**

According to note P to the directive 67/548/EEC, "Naphtha (petroleum)" is not to be classified as "carcinogenic" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 4 of 12

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

###### After inhalation

- Move to fresh air in case of accidental inhalation of vapours.
- Seek medical treatment immediately.

###### After contact with skin

- Wash off with soap and plenty of water.
- Consult a doctor if skin irritation persists.

###### After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Summon a doctor immediately.

###### After ingestion

- Do not induce vomiting.
- Rinse out mouth and give plenty of water to drink.
- Never give anything by mouth to an unconscious person.
- Summon a doctor immediately.
- The decision whether to induce vomiting or not is to be taken by a physician.

##### 4.2. Most important symptoms and effects, both acute and delayed

- May cause drowsiness or dizziness.
- Causes skin irritation.
- May damage the unborn child.
- Attention. Beware, danger of aspiration.
- Attention. Beware, danger of aspiration.

##### 4.3. Indication of any immediate medical attention and special treatment needed

- Treat symptoms.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

- Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

###### Unsuitable extinguishing media

- Full water jet.

##### 5.2. Special hazards arising from the substance or mixture

- Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>).

##### 5.3. Advice for firefighters

- Use breathing apparatus with independent air supply.
- Protective suit.

###### Additional information

- Cool containers at risk with water spray jet.
- The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
- Vapours are heavier than air and spread along ground.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### SECTION 6: Accidental release measures



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 5 of 12

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

- Use only explosion-proof equipment.
- Ensure adequate ventilation.
- Keep away sources of ignition.
- Keep away noninvolved persons.

##### **For non-emergency personnel**

- Do not breathe vapours.
- Avoid contact with skin, eyes and clothing.

##### **For emergency responders**

- In case of vapour formation use respirator.
- Use personal protective clothing.

#### **6.2. Environmental precautions**

- Do not discharge into the drains/surface waters/groundwater.
- Do not discharge into the subsoil/soil.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

- Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

- Observe protective instructions (see Sections 7 and 8).
- Informations for disposal look up chapter 13.

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

- Keep container tightly closed.
- Use only in thoroughly ventilated areas.
- Vapours are heavier than air and spread along ground.

##### **Advice on protection against fire and explosion**

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion protection rules.

##### **Hints on joint storage**

- Incompatible with oxidizing agents.

##### **Further information on storage conditions**

- Keep away from food, drink and animal feeding stuffs.

#### **7.3. Specific end use(s)**

Adhesive

## **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 6 of 12

#### Occupational exposure limits

| CAS No    | Substance   | ppm | mg/m <sup>3</sup> | fib/cm <sup>3</sup> | Category      | Origin |
|-----------|---|-----|-------------------|---------------------|---------------|--------|
| 1333-86-4 | Carbon black (Inhalable Fraction)                       | -   | 3                 |                     | TWA (8 h)     |        |
| 9006-04-6 | Natural Rubber Latex (as inhalable allergenic proteins) | -   | 0.0001            |                     | TWA (8 h)     |        |
| 1314-13-2 | Zinc oxide, fume (Respirable Fraction)                  | -   | 2                 |                     | TWA (8 h)     |        |
|           |   | -   | 10                |                     | STEL (15 min) |        |

#### 8.2. Exposure controls

##### Appropriate engineering controls

Pay attention to anti-explosion protection rules.  
Ensure adequate ventilation, especially in confined areas.

##### Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothing before re-use.

##### Eye/face protection

Tightly fitting goggles (EN 166).

##### Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by [www.kcl.de](http://www.kcl.de).  
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.  
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

##### Skin protection

Solvent-resistant apron (EN 467).

##### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid  
Colour: Black  
Odour: Hydrocarbon-like

#### Test method

pH-Value: n.d.

##### Changes in the physical state

Melting point/freezing point: n.d.  
Boiling point or initial boiling point and boiling range: 60 - 100 °C  
Sublimation point: n.a.  
Softening point: n.d.  
Flash point: - 18 °C  
Sustaining combustion: Sustaining combustion

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**PREMA BLACK VULC SOLUTION**

Revision date: 23.04.2024

Product code: 00623-0040

Page 7 of 12

**Flammability**

Solid/liquid: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: ~ 1,0 vol. %

Upper explosion limits: ~ 7,3 vol. %

Auto-ignition temperature: &gt; 250 °C

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

Vapour pressure:  
(at 20 °C) ~ 170 hPaDensity: 0,7497 g/cm<sup>3</sup>

Bulk density: n.a.

Water solubility:  
(at 20 °C) Immiscible**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: ~ 1000 mPa·s

Viscosity / kinematic:  
(at 40 °C) > 20,5 mm<sup>2</sup>/s

Flow time: &gt; 30 s 3 DIN/ISO 2431

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: 0 %

Solvent content: &lt; 85 %

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidising agents.

**10.4. Conditions to avoid**To avoid thermal decomposition, do not overheat.  
Heating can release vapours which can be ignited.  
Vapour/air-mixtures are explosive at intense warming.**10.5. Incompatible materials**

Oxidizing agents



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 8 of 12

#### **10.6. Hazardous decomposition products**

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

### SECTION 11: Toxicological information

#### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

##### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Naphtha (petroleum)

LD<sub>50</sub>/oral/rat: > 2000 mg/kg

LD<sub>50</sub>/dermal/rabbit: > 2000 mg/kg

LC<sub>50</sub>/inhalation: > 20 mg/l/4h

##### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

##### **Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

##### **Sensitising effects**

Based on available data, the classification criteria are not met.

Contains Di(benzothiazol-2-yl) disulphide, N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction.

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

May damage the unborn child. (Phenol, 4-(1,1-dimethylethyl)-, polymer with ethyne)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

##### **STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]; Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane])

##### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

##### **Aspiration hazard**

Based on available data, the classification criteria are not met.

##### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **11.2. Information on other hazards**

##### **Endocrine disrupting properties**

No data available

##### **Other information**

Contact with eyes may cause irritation.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

A longer or repeated contact may lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

### SECTION 12: Ecological information

#### **12.1. Toxicity**

Ecological data are not available.





## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 9 of 12

Naphtha (petroleum)  
LC50/fish: 1 - 10 mg/l  
EC50/Daphnia: 1 - 10 mg/l  
EC50/Algae: 10 - 100 mg/l  
Toxic to aquatic life with long lasting effects.

#### **12.2. Persistence and degradability**

Naphtha (petroleum)  
Liable to easy biological disintegration.

#### **12.3. Bioaccumulative potential**

Naphtha (petroleum)  
A bioaccumulation potential is to be expected.

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

Hazardous water pollutant

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

|   |           |
|---|-----------|
| <b><u>14.1. UN number:</u></b>                  | UN 1133   |
| <b><u>14.2. UN proper shipping name:</u></b>    | Adhesives |
| <b><u>14.3. Transport hazard class(es):</u></b> | 3         |
| <b><u>14.4. Packing group:</u></b>              | II        |
| Hazard label:                                   | 3         |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**PREMA BLACK VULC SOLUTION**

Revision date: 23.04.2024

Product code: 00623-0040

Page 10 of 12



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives (Naphtha (petroleum))  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Marine pollutant: Yes  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### PREMA BLACK VULC SOLUTION

Revision date: 23.04.2024

Product code: 00623-0040

Page 11 of 12

IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: < 85 %Information according to Directive  
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information: E2

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,11,12,15.

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation  
intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**PREMA BLACK VULC SOLUTION**

Revision date: 23.04.2024

Product code: 00623-0040

Page 12 of 12

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

| Classification          | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 2; H225      | On basis of test data    |
| Skin Irrit. 2; H315     | Calculation method       |
| Repr. 1B; H360D         | Calculation method       |
| STOT SE 3; H336         | Calculation method       |
| Aquatic Chronic 2; H411 | Calculation method       |

**Relevant H and EUH statements (number and full text)**

|        |  |
|--------|--|
| H225   | Highly flammable liquid and vapour.  |
| H302   | Harmful if swallowed.  |
| H304   | May be fatal if swallowed and enters airways.  |
| H315   | Causes skin irritation.  |
| H317   | May cause an allergic skin reaction.   |
| H319   | Causes serious eye irritation.   |
| H335   | May cause respiratory irritation.  |
| H336   | May cause drowsiness or dizziness.   |
| H360D  | May damage the unborn child.   |
| H360FD | May damage fertility. May damage the unborn child.   |
| H361f  | Suspected of damaging fertility.   |
| H400   | Very toxic to aquatic life.  |
| H410   | Very toxic to aquatic life with long lasting effects.  |
| H411   | Toxic to aquatic life with long lasting effects.   |
| EUH031 | Contact with acids liberates toxic gas.  |
| EUH208 | Contains Di(benzothiazol-2-yl) disulphide, N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction. |

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*